



POTS Adapter

Convert your hard-to-maintain Plain Old Telephone System to cost-effective VoLTE infrastructure



Made for Industrial Use

Compatible with alarms, elevators, and communications systems, the adapter can squeeze into any deployment without worry.

The POTS Adapter's low power consumption makes it suitable for solar powered deployments.



Elevator Phones



Alarms connected to emergency services



Fax Machine



AutoDial Support



Door/Gate



Roadside Call Boxes

InControl Remote Management

Track and manage the status of all your devices remotely, all from the same management system.

Automatically send email alerts to admins when device off line or changes to power supply are detected.

Receive Peplink support via remote assistance. No physical presence needed for troubleshooting.





Minimal Power Consumption

Low power consumption translates to reduced operating costs and less heat generation, increasing the device's longevity and reliability.









125.7mm

Built for Flexibility

The POTS Adapter is designed to be small, lightweight, and mountable on a DIN Rail. Connect an external antenna to maximize performance in secluded installs.

Easily Scalable

Bring VoLTE to numerous deployments without breaking the bank.







Flexible Power Options

Power the device via USB-C or 4-pin Molex depending on available resources on-site. Or use both at the same time for extra redundancy.



Primary Benefit:

Easily Convert your Plain Old Telephone System (POTS) connections to LTE Cellular.



Plug and Play

Drop in Peplink's POTS to Cellular Adapter to update your legacy analog phone line connections to cellular. Requires only a power source and cellular network signal.





2 Certified for industrial and commercial applications


Alarm systems, elevators, remote door/gate systems and other legacy applications utilizing analog phone lines. Rugged, low power consumption and operates across wide temperature range.



ATB#

Reliable and cost effective

Deploys standalone, no additional network equipment or setup required. Complete central management and alerting through Peplink InControl2 reduces deployment and troubleshooting costs.



POTS Adapter





Specifications

WAN Interface	1x LTE Embedded Cellular Modem	Communication Protocols	Contact ID Pulse 4/2
Configuration Interface	USB-C Port		Voice: G.711, G.729, AMR, AMR-WB Fax: ITU-T.30, V.17, V.29, V.27ter, V.21
POTS line	Up to 3 REN Line Load 55 V _{rms} Ring Voltage	Power Consumption	1.7W (nominal), 3.5W (max.)
	500ft Loop Length Support	Dimension	5.0 x 4.2 x 1.4 inches / 124 x 107 x 35 mm
Antenna Connectors	2x SMA Cellular Antenna Connectors	Weight	0.70 pound / 0.32kg
Power Input	Power Port: 9-16V DC USB-C Port: 5V DC	Operating Temperature	-22° – 149°F / -30° – 65°C
		Humidity	15% – 90% (non-condensing)
Backup power by UPS ¹	3000 mAh UPS will ensure:		
	- 24 Hours Standby Usage	Certifications	FCC, RoHS, UL
	- 4 Hours Under Line Usage		4 007041
Material Francisco	A 11 (15) (1	Package Content for	1x POTS Adapter
Voice Features	Audio notifications	POTS-ADP-LTE-US-T-PRM	2x LTE Antennas
	Call Forwarding (CFU/CFB/CFNRy/CFNRc) Call Hold		1x 12V 2A 4-Pin Power Supply (ACW-632)
	Call Waiting	Package Content for	1x POTS Adapter
	3-Way Conference	POTS-ADP-LTE-US-DC-T-PRM	2x LTE Antennas
	CLIR per Call	10107151 212 00 50 1 1 1 1 1 1	1x 10ft DC Power Cable (ACW-634)
	Speed Dial 8/30		
	Call Return	SIM Option ²	1x Nano-SIM (4FF)
	Call Blocking	•	
	Do Not Disturb	Warranty	1-Year Limited Warranty
	Caller ID		
	VMWI		

DTME

¹ UPS is not included into packing list. ² Data-only SIM is not supported.

POTS Adapter



Ordering Information

Product Code Regions LTE Bands

POTS-ADP-LTE-US-T-PRM North America* B2, B4, B5, B12, B13, B14, B66, B71

*US Carrier Certifications: Verizon, AT&T, T-Mobile, FirstNet

POTS-ADP-LTE-US-DC-T-PRM North America* B2, B4, B5, B12, B13, B14, B66, B71

*US Carrier Certifications: Verizon, AT&T, T-Mobile, FirstNet

Featured Add-on

Product Code Description

PRM-A-1Y / PCP-A-1Y PrimeCare A / PrimeCare+ A (1-Year)

PRM-A-2Y / PCP-A-2Y PrimeCare A / PrimeCare+ A (2-Year)

PRM-A-4Y / PCP-A-4Y PrimeCare A / PrimeCare+ A (4-Year)

ACW-634 10ft DC Power Cable

ACW-791 Peplink 4-Pin Molex to USB-C power cable

ACW-DIN-BR1-MINI DIN Rail Mount Kit

ANT-MB-20G-S-B-6 Mobility 20G - 2x2 MIMO LTE/5G-Ready Cellular Antenna System with GPS (Black)

ANT-MB-20G-S-W-6 Mobility 20G - 2x2 MIMO LTE/5G-Ready Cellular Antenna System with GPS (White)